



C-BAND ACTIVE RADAR CALIBRATOR

Space Applications Centre (SAC) of Indian Space Research Organisation (ISRO) has developed a C-band active radar calibrator for calibration of microwave imaging sensors. It is a ground based equipment developed indigenously.

Salient Features

- ARC can calibrate individual Like and Cross-Polarised C-band SAR Channels; W, HH, VH, HV & Circular Polarisation using two ARC Rxs.
- Dual Polarized broadband (7%) multilayer microstrip antenna of 23 dB gain and cross polarization better than -40 dB.
- Antenna protected by radome using inverted patch.
- Receiver Input Signal range: -25 to -60 dBm, Max Tx signal: + 20dBm.
- Each Channel contains Selectable Gain with Digital control (Step: 1dB) & 6 bit Digital Phase Control in steps of 0.625 deg.

Technology Transfer

SAC/ISRO offers to transfer this technology of the **C band Active Radar Calibrator** developed by SAC to industries in India with adequate experience and facilities. Enterprises interested in obtaining knowhow may register and submit their proposal to IN-SPACe, Ahmedabad at www.inspace.gov.in

For more details, Contact:

Technology Transfer & Industry Interface Division (TTID), PPEG
Space Applications Centre (SAC), ISRO
Ambawadi Vistar, Jodhpur Tekra, Ahmedabad - 380 015
Email: ttid@sac.isro.gov.in
https://www.sac.gov.in/SAC_Industry_Portal

